

High Reliability Kiosk Printer

NP-2511



NP-3511



Model | NP-2511 / NP-3511

Specifications

Model	NP-2511	NP-3511
Print method	Line thermal dot	
Print speed	Max. 200 mm/sec	
Resolution	8 dots / mm (203dpi)	
Number of dots/line(dots)	416 (Default), 432	576 (Default), 560
Paper width	58 (Default), 60 mm	80 (Default), 65, 76, 82.5mm
Print width	52 (Default), 54, 56mm	72 (Default), 59, 70, 80mm
Paper diameter	Max. 83 mm	Max. 83 mm
Character	International, English, Greek, Polish, Russian, Scandinavian, Turkish, Chinese, Korean, Japanese	
Barcode	UPC-A / UPC-E / EAN-13 / EAN-8 / CODE39 / ITF / CODABAR / CODE128	
Interface	USB (V2.0 FULL SPEED) and Serial (RS232C)	
Drivers	Windows® XP / Vista / 7 / CE 6.0, Linux (CUPS)	
Cutter	Full cut and Partial cut *by command	
Operating voltage	DC 24 V	
External dimensions	106(W)x150(D)x75(H)mm	127(W)x150(D)x75(H)mm

Application

Queue Management System

Information KIOSK

Coin-locker system

Features

Paper width

2-inch

3-inch

Paper loading

Auto loading

Openable head

Paper cutter

Auto cutter

Lock free cutter

High Speed printing : Max. 200mm/sec.

Paper thickness up to 150 micrometer

Capable of using presenters

12V version (NP-2521) is newly available.

CONSULTING DISTRIBUTOR



POHL Electronic GmbH
Eduard-Maurens-Straße 11a • 16761 Hennigsdorf
Tel. +49 3302 81893-0 • Fax +49 3302 81893-99
www.pohl-electronic.de • info@pohl-electronic.de



NP-2511V



NP-3511V