


High Reliability Kiosk Printer

NP-3611



Features

Paper width

2-inch

3-inch

Paper loading

Auto loading

Openable head

Paper cutter

Auto cutter

Gradation: 16 Gray Scale Picturesque Printing Lock free cutter

High Speed printing : Max. 250mm/sec.

Paper thickness up to 150 micrometer

Capable of using presenters

Option: Transmission sensor for labels is attachable

Model

NP-2611 / 3611

Specifications

Model	NP-2611	NP-3611
Print method	Line thermal dot	
Print speed	Max. 250 mm/sec	
Resolution	8 dots / mm (203dpi)	
Gradation	16 gray scale	
Number of dots/line(dots)	576 (Default), 560, 640	576 (Default), 560, 640
Paper width	58 (Default), 60 mm	80 (Default), 76
Print width	52 (Default), 54, 56 mm	72 (Default), 70, 80 mm
Paper diameter	120 mm, 150mm	
Character	International, English, Greek, Polish, Russian, Scandinavian, Turkish, Chinese, Korean, Japanese	
Barcode	UPC-A / UPC-E / EAN-13 / EAN-8 / CODE39 / ITF / CODABAR / CODE128 / QR code (model2) / PDF417	
Interface	USB (V2.0 FULL SPEED) and Serial (RS232C)	
Cutter	Full cut and Partial cut *by command	
Operating voltage	DC 24 V	
External dimensions	106(W)x151(D)x87(H) mm	128(W)x151(D)x129(H) mm

CONSULTING DISTRIBUTOR



POHL

POHL Electronic GmbH
Eduard-Maurer-Straße 11a • 16761 Hennigsdorf
Tel. +49 3302 81893-0 • Fax +49 3302 81893-99
www.pohl-electronic.de • info@pohl-electronic.de