

Face Mount Printer

NP-F369



Features

Paper width

3-inch

Paper loading

Auto loading

Paper cutter

Auto cutter

Lock free cutter

High Speed printing : Max. 250mm/sec.

Paper thickness up to 150 micrometer

Capable of using presenters

Gradation: 16 Gray Scale Picturesque Printing

Option: Transmission sensor for labels is attachable

Model NP-F369

Specifications

Model	NP-F369
Print method	Line thermal dot
Print speed	Max. 250 mm/sec
Resolution	8 dots / mm (203dpi)
Number of dots/line(dots)	576 (Default), 640
Paper width	80 (Default)
Print width	72 (Default), 80 mm (Max)
Paper diameter	120 mm, 150 mm
Gradation	16 Gray Scale
Character	International, English, Greek, Polish, Russian, Scandinavian, Turkish, Chinese, Korean, Japanese
Barcode	UPC-A / UPC-E / EAN-13 / EAN-8 / CODE39 / ITF / CODABAR / CODE128 / QR code (model2) / PDF417
Interface	USB (V2.0 FULL SPEED) and Serial (RS232C)
Cutter	Full cut and Partial cut *by command
Operating voltage	DC 24V
External dimensions	139.6(W)x87(D)x71(H)mm

CONSULTING DISTRIBUTOR



POHL

POHL Electronic GmbH
Eduard-Maurer-Straße 11a • 16761 Hennigsdorf
Tel. +49 3302 81893-0 • Fax +49 3302 81893-99
www.pohl-electronic.de • info@pohl-electronic.de