



MP-A40 SERIES MOBILE PRINTER



Seiko Instruments tough and stylish mobile printer series is designed to support applications even under rough conditions. Still it is simple to operate with the latest systems including Windows, Android and iOS.

"Made for iPod", "Made for iPhone", "Made for iPad" mean that an electronic accessory has been designed to connect specifically to iPod, iPhone and iPad respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards.

MP-A40 SERIES

Mobile Printer

- Withstands multiple drops from up to 2 meters
- Protection rating IP54
- -20°C to 50°C operating temperature
- 105mm/s max. printing speed
- Stylish design with large control buttons and LED'S for simple operation
- Wide variety of driver and SDK for mobile equipment



Measuring Instrument



PDA/ Smart Device



Barcode



Portable Printer



Label



Medical Equipment



Model	MP-A40	
Printing	Method	Thermal line dot printing
	Number of dots/line	832
	Resolution (dots/mm)	203 (8 dots / mm)
	Paper width (mm)	80 ⁺⁰ ₋₁ / 100 ⁺⁰ ₋₁ / 105 ⁺⁰ ₋₁ / 112 ⁺⁰ ₋₁
	Printing width (mm)	104
	Speed (mm/sec) max	105
	Outside diameter of paper roll (mm) max	Ø 58
	Character matrix (HxW mm)	24 x 12, 24 x 24, 16 x 8, 16 x 16
	Character dimensions (HxW mm)	3.0 x 1.5, 3.0 x 3.0, 2.0 x 1.0, 2.0 x 2.0
Type of Paper	Roll paper, Label roll paper	
Character type	Code page: 17pages, Katakana character, Option font, Downloaded character, User-dened character, JIS 1 & 2 level kanji	
Bar code	UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128, PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar	
Power supply (V)	Option : specified AC adapter, Li-Ion battery	
Communication interface	Communication interface USB, Bluetooth [*] , WLAN ^{* 1}	
Input buffer	4k bytes	
Command	ESC/POS™ conformity, CPCL conformity, Markup Language	
Cutting	Tear bar	
Drop rating	2.0m (6.6feet) multiple* ²	
IP rating	IP54* ²	
Operating temperature (°C)	-20 to 50	
Service life (km)	50* ³	
Dimensions (WxDxH mm)	156 x 152 x 71* ⁴	
Mass (g)	Approx. 760* ⁵	
Standard	FCC, CE, VCCI	
Included accessories	AC Adapter, AC cable, Battery pack, USB cable, Thermal paper sample roll	
Optional accessories	Battery charger (single/quad), Serial cable, Car charger, Shoulder strap, Specified phenol free Thermal paper, Thermal labels (4x2", 4x3", 4x4", 4x6")	
Software	Printer driver, Windows [*] CE(SDK), Android™(SDK), iOS	

*1 Selected model. *2 test performance by specified condition. *3 Use recommended thermal papers. *4 Excluding protrusion *5 Including battery, excluding roll paper

ESC/POS™ is a registered trademark of SEIKO EPSON Corporation.
Windows® is a registered trademark of Microsoft Corporation(USA).
Android™ is a trade mark of Google Inc.

Specifications are subject to change without notice.



CONSULTING DISTRIBUTOR
POHL

POHL Electronic GmbH
Eduard-Maurer-Straße 11a • 16761 Hennigsdorf
Tel. +49 3302 81893-0 • Fax +49 3302 81893-99
www.pohl-electronic.de • info@pohl-electronic.de