

HF800-OE

Fixed-mounting 2D Industrial Reader

The new fixed-mounting industrial reader HF800-OE delivers outstanding barcode reading capability for all types of 1D and 2D codes including those on printed labels and the most difficult direct part mark (DPM), making it perfect for production data tracking for PCB and precision electronic parts, food production process management and confirmation of logistics barcode on the external packing cartons for electric/mechanical parts.

HF800-OE is equipped with imager with a resolution of 500K-pixel which is capable of collecting images at 60 fps. Its built-in red LED light source combined with exceptional DPM decoding algorithm enables HF800-OE to have powerful DPM resolution. In addition, its compact size makes it ideal for use in industrial environment with limited space. The IP65 protection rating also ensures that it can handle various harsh working environments.

HF800-OE is also equipped with DataMax software, as well as AutoLearn function. The user can complete image setting with just one button, a significant convenience for any bar code reader.

The device is integrated with network ports, RS232 port and RS485 port as well as I/O port input to meet the needs of users in different application environments. A 0-degree and 90-degree version for vertical or horizontal mounting can be selected based on the site's actual working needs.



Depending on the working distance, there are 3 different versions available– HD, SR and ER. The user can select a product that suits their needs for working distance and field of vision.

CONSULTING DISTRIBUTOR



POHL

POHL Electronic GmbH
Eduard-Maurer-Straße 11a • 16761 Hennigsdorf
Tel. +49 3302 81893-0 • Fax +49 3302 81893-99
www.pohl-electronic.de • info@pohl-electronic.de

Features & Benefits



Powerful DPM decoding: 500K-pixel resolution imager with 60fps capability and built-in red LED light source to give it powerful decoding capability for DPM.



Suitable for use in harsh and complex environments: Its compact size makes it ideal in tight industrial environment, while its IP65 rating ensures that it can handle all types of harsh and complex work environments.



Simple and quick configuration: Equipped with DataMax software and AutoLearn functions, it allows image setting to be completed with just one button, thereby significantly increasing the convenience of configuring the reader.



Wide variety of ports: HF800 is integrated with network port, RS232 port and RS485 port, as well supports I/O port output.



Numerous models to meet different application needs: Offers two versions – 0° and 90° – as well as 3 versions namely HD, SR and ER for different distances*; product combinations meet the needs of users for different applications.

HF800-OE Fixed-mounting 2D Industrial Reader Technical Data

HF800-OE Key Technical Data

Description	Horizontal	Vertical
Dimensions	54.5*52.5*29mm	73.2*52.5*29mm
Weight (device only)	210g	265g
Housing Material	Zinc alloy	
Decoding Performance	1D bar code, PDF417 2D codes: QR Code, Data matrix, Maxi code, Aztec	
Imager	838*640 CMOS chip Global shutter	
Imaging Speed	60fps	
Available Models	3 versions for different work distance and FOV: HD, SR and ER	
Learning Button	Includes learning button for quick setting	
Aiming Device	0° – Laser indicator; 90° – LED indicator	
Dispersed Input	2*photoelectric dispersed input; definition can be programmed	
Dispersed Output	2*photoelectric dispersed output; definition can be programmed	
Status Output	Five-status LED, buzzer	
Power	Standard 10VDC-30VDC	
Power Consumption	Max 5W	
Communication	RS232, RS485 and Ethernet ports	
Network mode	Master / Slave	
Operating Temperature	0 °C to 50 °C	
Storage Temperature	-20 °C to 70 °C	
IP Rating	IP65	
Operating System	Windows XP, Vista, Windows 7,10	

Typical performance for HD, SR and ER models*

HF800HD-OE	0 degree	90 degree
4mil Code 39	50~80mm	25~55mm
5mil Code 39	30~115mm	25~90mm
13 mil UPC	40~175mm	25~150mm
10 mil datamatrix	22~128 mm	25~105mm
20 mil datamatrix	23~195mm	25~170mm
HF800SR-OE	0 degree	90 degree
5mil Code 39	64~140mm	39~115mm
13 mil UPC	55~405mm	30~380mm
10 mil datamatrix	62~190mm	37~165mm
20 mil datamatrix	47~375mm	25~350
HF800ER-OE	0 degree	90 degree
5mil Code 39	147~218mm	122~193mm
13 mil UPC	71~480mm	46~455mm
10 mil datamatrix	135~250mm	110~225mm
20 mil datamatrix	102~400mm	77~375mm

* Can be influenced by barcode quality and environmental conditions



CONSULTING DISTRIBUTOR



POHL Electronic GmbH
 Eduard-Maurel-Straße 11a • 16761 Hennigsdorf
 Tel. +49 3302 81893-0 • Fax +49 3302 81893-99
 www.pohl-electronic.de • info@pohl-electronic.de

For more information please visit:

www.honeywellaidc.com.cn

Honeywell Safety and Productivity Solutions

Pudong New District, Shanghai

No. 555, Huanke Road, Zhangjiang Hi-tech Park

Nationwide Purchase Hotline: 400 639 6841

HF800-OE DS Rev A 09/20
 © 2020 Honeywell International Inc.



Honeywell