

MS7120 Orbit

Omnidirectional Laser Scanner

Honeywell's MS7120 Orbit [®] provides aggressive omnidirectional scanning in an award-winning design for retailers seeking an affordable, aesthetically pleasing scanning solution.

Orbit, the all-time, best-selling hands-free omnidirectional scanner, presents an innovative, elegant and affordable solution to convenience retail applications where counter space is at a premium.

Compact, lightweight and rugged, Orbit maximizes customer satisfaction and employee efficiency with a patented 20-line scan pattern, an easy-to-find sweet spot and a scan speed of 1,120 scans per second.

The scanner's expanded ability to update its firmware via Honeywell's patented MetroSet [®] 2 configuration software (provided free) safeguards long-term infrastructure commitments in the event of a change in the POS system or software.

Recipient of multiple design honors, Orbit's award-winning shape enables hand-held scanning of large, bulky items. For added flexibility, the scanning head can be tilted within a 30° range to accommodate objects of various sizes and shapes.

Standard features include user-replaceable cables, Honeywell's patented MetroSelect and MetroSet [®] 2 for easy configuration, data editing and OPOS/JPOS compatibility for easy installation.

For more information on the MS7120 Orbit omnidirectional laser scanner, please visit www.honeywell.com/aidc



Features

- 20 Scan Line Omnidirectional Pattern: Provides aggressive scanning as an additional benefit to hand presentation applications
- Sweet Spot Scanning: Engineered "sweet spot" to optimize scan performance and first pass read rate
- Adjustable Scan Head: Ability to tilt scanner 30° for targeted scanning or larger products
- Flash ROM: Protects POS investment with free firmware updates via MetroSet [®] 2 software and standard PC
- Automatic Scanning Operation: Simply present a bar code and the unit scans in a single pass

MS7120 Orbit Technical Specifications

Operational

Light Source	Visible Laser Diode 650 nm \pm 10 nm
Visual Indicators	Blue = ready to scan; White = good read
Host System Interfaces	USB, RS232, Keyboard Wedge, IBM 468xx (RS485), Light Pen Wand Emulation

Mechanical

Dimensions (LxWxH)	105 mm x 102 mm x 150 mm (4.1" x 4.0" x 5.9")
Weight	400 g (14.1 oz)

Electrical

Input Voltage	5 VDC \pm 0.25 V
Operating Power (typical)	900 mW (180 mA @ 5 V)
Standby Power (typical)	850 mW (170mA @ 5 V)
DC Transformers	Class 2: 5.2 VDC @ 1 A
Laser Class	Class 1: IEC60825-1, EN60825-1
EMC	FCC Part 15, ICES-003, EN55022 Class B

Environmental

Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-40°C to 60°C (-40°F to 140°F)
Humidity	5% to 95% relative humidity, non-condensing
Drop	Designed to withstand 1.2 m (4') drops
Environmental Sealing	Sealed to resist airborne particulate contaminants
Light Levels	4842 Lux (450 foot-candles)

Scan Performance

Scan Pattern	Omnidirectional: 5 fields of 4 parallel lines
Scan Speed	1120 scan lines per second
Print Contrast	35% minimum reflectance difference
Pitch, Skew	60°, 60°
Decode Capability	Reads standard 1D and GS1 DataBar symbologies. Visit www.honeywell.com/aidc/symbologies for details.
Warranty	3 year factory warranty



For more information:
www.honeywell.com/aidc

Honeywell Security & Data Collection
Honeywell Scanning & Mobility
90 Coles Road
Blackwood, NJ 08012
856.228.8100
www.honeywell.com

Typical Performance*	
Narrow Width	Depth of Field
5.2 mil	25 mm - 50 mm (1.0" - 2.0")
7.5 mil	0 mm - 150 mm (0" - 5.9")
10 mil	0 mm - 175 mm (0" - 6.9")
13 mil	0 mm - 215 mm (0" - 8.5")
26 mil	25 mm - 250 mm (0" - 9.8")
*Resolution: 5 mil (0.125 mm)	
*Performance may be impacted by bar code quality and environmental conditions	

Honeywell