

# VOYAGER EXTREME PERFORMANCE (XP) 1470g



**POHL**

CONSULTING DISTRIBUTOR

POHL Electronic GmbH  
Eduard-Maurer-Straße 11a • 16761 Hennigsdorf  
Tel. +49 3302 81893-0 • Fax +49 3302 81893-99  
www.pohl-electronic.de • info@pohl-electronic.de

Durable, Highly Accurate 2D Scanner

Designed for in-store retail environments requiring a highly accurate 2D scanning solution in a durable form factor, the Voyager™ Extreme Performance (XP) 1470g scanner delivers industry-leading scanning capability on traditional barcodes and digital screens – even on damaged and difficult-to-read codes.

With better durability and a more powerful scan capability than previous models – or any competitive scanner in its class – the Voyager XP 1470g scanner is the perfect option for workflows that include 1D and 2D barcode reading and require a more robust and reliable solution. The Voyager XP 1470g scanner combines added durability and better scan capability at the same competitive price point as its predecessor. The scanner's extended scan distance will reach right to the bottom of the cart without bending and wasted time at the checkout.

Built on the platform of Honeywell's iconic Voyager series handheld scanners, the Voyager XP 1470g scanner is fully backward-compatible with existing Voyager accessories, reducing total cost of ownership.

Engineered to 30 drops at 1.8 m (6 ft) and 1,000 tumbles at 0.5 m (1.6 ft), the Voyager XP 1470g scanner is built to withstand busy point-of-sale scanning with much better accuracy than comparable solutions.



*The Voyager XP 1470g scanner combines enhanced reading of poor-quality and damaged codes with class-leading durability, reducing the risk of errors and operational slowdowns and avoiding the hidden cost of warranty.*

## **DISINFECTANT-READY HOUSINGS – NEW!**

Select models now available with disinfectant-ready housings. These models can be cleaned regularly with a wide variety of cleaning solutions without damaging your product.

## FEATURES AND BENEFITS



Highly accurate and fast scanning of even damaged and poor-quality barcodes, with an extended scan distance to reach the bottom of the cart without bending and wasted time at point of sale.



Enhanced performance on the codes stores scan every day, including digital coupons, codes, and wallets on customers' smartphones, as well as merchandise codes at the register.



Honeywell Operational Intelligence software delivers on-demand scan insights, enabling higher employee productivity and throughput.



The Honeywell Scanner Management Utility (SMU) creates a holistic solution that automates deployment and updating of the scanner.

**Honeywell**

# Voyager XP 1470g Technical Specifications

## MECHANICAL/ELECTRICAL

**Dimensions (L x W x H):** 62 mm x 169 mm x 82 mm (2.4 in x 6.6 in x 3.2 in)

**Scanner Weight:** 130 g (4.6 oz)

**Input Voltage:** 4.0V DC to 5.5V DC

**Operating Power:** 2 W (400 mA @ 5V DC)

**Standby Power:** 0.45 W (90 mA @ 5V DC)

**Host System Interfaces:** USB, Keyboard Wedge, RS-232, RS485 support for IBM 46xx (RS485)

## ENVIRONMENTAL

**Operating Temperature:** 0°C to 50°C (32°F to 122°F)

**Storage Temperature:** -40°C to 60°C (-40°F to 140°F)

**Electrostatic Discharge (ESD) (Scanners and Cradles):** ±8 kV indirect coupling plane, ±15 kV direct air

**Humidity:** 0% to 95% relative humidity, non-condensing

**Tumble Spec:** 1,000 0.5 m (1.6 ft) tumbles (impacts)

**Drop:** Engineered to withstand 30 1.8 m (6 ft) drops to concrete

**Environmental Sealing:** IP52

**Light Levels:** 0 to 100,000 lux (9,290 foot-candles)

## SCAN PERFORMANCE

**Scan Pattern:** Area Image (1040 x 720 pixel array)

**Motion Tolerance:** 70 cm/s (27.6 in/s) for 13 mil UPC at optimal focus

**Scan Angle:** Horizontal: 39.2° nominal; Vertical: 27.4° nominal

**Roll, Pitch, Skew:** ±180°, ±65°, ±70°

**Print contrast:** 20%

**Decode Capabilities:** Reads standard 1D, PDF, 2D, and DotCode symbologies  
Note: Decode capabilities dependent on configuration.

**Warranty:** 5-year factory warranty

For a complete listing of all compliance approvals and certifications, please visit [www.honeywellaidc.com/compliance](http://www.honeywellaidc.com/compliance).

For a complete listing of all supported barcode symbologies, please visit [www.honeywellaidc.com/symbologies](http://www.honeywellaidc.com/symbologies).

Voyager is a trademark or registered trademark of Honeywell International Inc.

All other trademarks are the property of their respective owners.

## DECODE RANGES (DoF)

TYPICAL PERFORMANCE*	STANDARD RANGE (SR)
5 mil Code 39	20 mm – 205 mm (0.8 in – 8.1 in)
13 mil UPC	18 mm – 400 mm (0.7 in – 15.8 in)
6.7 mil PDF417	15 mm – 185 mm (0.6 in – 7.3 in)
10 mil DM**	10 mm – 165 mm (0.4 in – 6.5 in)
20 mil QR	5 mm – 325 mm (0.2 in – 12.8 in)

\* Performance may be impacted by barcode quality and environmental conditions.

\*\* Data Matrix (DM)

## For more information

[www.honeywellaidc.com](http://www.honeywellaidc.com)

## Honeywell Safety and Productivity Solutions

300 S Tryon St Suite 500

Charlotte, NC 28202

877-841-2840

[www.honeywell.com](http://www.honeywell.com)

## CONSULTING DISTRIBUTOR



**POHL**

POHL Electronic GmbH

Eduard-Maurer-Straße 11a • 16761 Hennigsdorf  
Tel. +49 3302 81893-0 • Fax +49 3302 81893-99  
[www.pohl-electronic.de](http://www.pohl-electronic.de) • [info@pohl-electronic.de](mailto:info@pohl-electronic.de)