

Mobile Printer

DPU-S Series



- Max **printing** speed: 100mm/sec (DPU-5245)
90mm/sec (DPU-S445)
- Interface: Bluetooth®, USB, Serial
- Compact and light-weight
- Easy paper operation
- Wide variety of driver and **utility software** suite



Made for
iPod iPhone iPad

Model	DPU-S245	DPU-S445
Method	Thermal line dot printing	
Number of dots/line	384	832
Resolution (dots/mm)	8	
Paper width (mm)	58 ^{±0.1}	112
Printing width (mm)	48	104
Speed (mm/sec) max	100	90
Outside diameter of paper roll (mm) max	φ 38	φ 50
Character matrix (HxW dots)	24 x 12, 24 x 24, 16 x 8, 16 x 16	
Character dimensions (HxW/mm)	3.0 x 1.5, 3.0 x 3.0, 2.0 x 1.0, 2.0 x 2.0	
Number of columns	24, 12, 32, 16	52, 26, 69, 34
Type of Paper	Roll paper, Label roll paper	Roll paper, Label roll paper, Cut sheet paper
Character type	Extended graphics character set, Katakana character set, CP1252, Optional font, Downloaded character, User-defined character, JIS 1 & 2 level kanji	
Barcode	UPC-A/E, JAN (EAN) 8/1:3, ITF, CODE39, CODABAR, CODE128, PDF417, QR Code, MaxiCode, Data Matrix	
Power supply (V)	Li-Ion battery, Specified AC adapter	
Communication interface	Bluetooth [®] , USB, Serial	
Input buffer	4K bytes	
Command	ESC/P™ conformity	
Cutting	Tear bar	
Operating temperature (°C)	-10 to 50	0 to 50
Service life (kml)	50 ²	
Dimensions (WxDxH mm)	83 x 130 x 45 ¹⁾	145.0 x 135.0 x 55.0 ¹⁾
Mass (g)	Approx. 280 ¹⁾	Approx. 490 ¹⁾
Standard	FCC, CE, VCCI, CCC,	
Option	AC adapter, Battery pack, Battery charger, AC cable, USB cable, Serial cable, Carrying case	
Software ⁶⁾	Printer driver, Windows® CE (SDK), Android [®] (SDK), iOS (SDK)	

¹⁾ Only Bluetooth® model. ²⁾ Recommended thermal papers. ³⁾ Excluding protrusion. ⁴⁾ Including battery, excluding roll paper. ⁵⁾ DPU-S445-008-E model only. ⁶⁾ Please refer to the official home page "www.seiko-instruments.de" for details.

Serial interface specification

Item	Specification
Baud rate	1200, 2400, 4800, 9600, 19200, 38400, 57600, 115200 bps
Data bit	7bits, 8bits
Parity bit	Odd, Even, or None
Stopbit	1bit, 2bits
Control method	H/W BUSY, Xon/Xoff

USB interface specification

USB printer-class 2.0 conformity

Bluetooth® interface specification

Based on Bluetooth® Ver. 2.1 + EDR

Easy paper operation



Cut sheet paper



S11

Seiko Instruments GmbH
Siemensstraße 9
0-63263 Neu-Isenburg, Germany
Phone +49 6102 297 0
info@seiko-instruments.de
www.seiko-instruments.de



SEIKO
SEIKO HOLDINGS GROUP

CONSULTING DISTRIBUTOR

POHL

POHL Electronic GmbH
Eduard-Maurer-Straße 11a • 16761 Hennigsdorf
Tel. +49 3302 81893-0 • Fax +49 3302 81893-99
www.pohl-electronic.de • info@pohl-electronic.de